



GENERAL NOTES

TRAFFIC CONTROL DEVICES SHALL COMPLY WITH THE MUTCD.

contractor shall maintain a minimum lane width of 12' at all times for any open lane of traffic.

DEPONENT OF THIS PROCESS.

A 5 WES SEGDANT HIGH IS RESIDENT TO THE WORK MAY, AND WES SEGDANT HIGH IS THE PROCESS.

SHALL SE WANTENDS PROCESSOR THE DUNBRIDGE OF THE WORK MAY, AND WEST SEGDEN WITH THE PROCESSOR OF THE WORK MAY, AND WEST SEGDEN WITH THE WORK MAY HE SOUTHWAY HAS SOUTHWAY HAS SOUTHWAY HAVE A SOUTHWAY HAVE


WORK SHALL BE COMPLETED BETWEEN 7:00AM AND 7:00PM

TRAFFIC CONTROL DEVICE LEGEND

PLACE STANDARD HIGHWAY SIGN (MUTCD SIGN ∯ R9−11 SHOULD READ "SIDEWALK CLOSED AHEAD CROSS HERE"). SIGN SHALL BE 24" X 24" MIN.

Notes for Figure 6H-28—Typical Application 28 Sidewalk Cleaures and Bypass Sidewalks Street lighting may be considered.

Doly the PTG device relief to predoctions are shows. Other devices, ware no late cleasure against probability of the probability







Interior Design

Planning Sustainability

2801 Woodard Drive, Suite 10: Columbia, MO 65202 573.443.1407

www.soa-inc.com

Missouri Certificate of Authority Number: 000826

Professional Building East 280 LLC

Walnut

12/15/2016 REVISION DATE 01/30/2017

PEDESTRIAN CONTROL PLAN (PHASE 1)

TC₂

SOA PROJECT 15025